

Product Code

MR22,MR25



Technical Description

The complete solution...

- Introducing Mons-D Louvre LED Trunking system; clean and sleek design aesthetic ideal for commercial, architectural and residential lighting applications
  - Saving energy: Improved efficiency, up to 70lm/W at CRI90
  - Saving installation costs: Modular and tool-free operation
  - Saving maintenance costs: 5 years warranty\*
  - Amazing add-on features: Emergency/Sensor/Dimming/Track modules
  - Pre-wired trunking rail with 7 wires and 3 pins for easy phase selection
  - For more information watch the Video [here](#)
  - If you require a customised version of this product, please [contact us](#)
- \*Please see Warranty Terms & Conditions for further information.

Electrical Specifications



System Power	21W, 27W, 30W, 37W
Input Voltage	240V
Control Type	ON/OFF, 0-10V, DALI, Casambi
System Efficacy (max.)	70lm/W
Power Factor	> 0.9

Physical Characteristics

Installation Method	Surface Mounted / Suspended
Trim Finish	White, Black
IP Rating / IK Rating	IP50/ IK05
Accessories	Black Louvre, White Louvre
Weight	4.2Kgs
Fitting Material	Aluminium

Photometric Info

Luminaire Lumens	1470lm, 1890lm, 2100lm, 2590lm
CRI	CRI90
CCT	3000K, 4000K
Beam Angle	76°
Lumen Maintenance	> 54, 000hrs (L70 B30)
MacAdam Step	3 Step



Polar Distribution Diagrams

Mons-D Louvre 76°

